

SINGLE SCISSOR

FLEXIBLE

ADAPTABLE

POWERFUL



LIFT SOLUTIONS CAN BE FOUND AT EDMOLIFT

Our largest product group is made up of simple, yet powerful and versatile lift tables. These single scissor models can be found in a host of different operations, all equally adaptable, stable and ergonomic in design. The lift table is often used as a means for material handling directly on the production floor or as a lorry loader outdoors at a loading dock.

With a variety of performances and models, not to mention a load capacity of between 500 kilos and 10 tons, there is a lift table for every need. It is not just industry that is a major user - we also deliver to distribution centres, warehouses, stores and other service establishments. All models in the single scissor product group that start with T (T models) can be customized to the end-users specific requirements. The lift table can be supplied in a variety of different colours, with a host of different accessories or control alternatives all designed to suit the individual requirements of the customer. A number of models can be of the heavy-duty variety suitable for use in intensive operations.

Functionality of the product can be increased with the help of a number of accessories. Examples of such accessories within the product group are: mobile base, load flaps, guard rails, roller conveyors and turntables. For further information, see our product leaflet "Accessories".

At EdmoLift you can find solutions for your lifting problems.

PRODUCT FEATURES

- ◆ Load capacity max 10 000 kg.
- ◆ Platform length from 900 mm to 5000 mm in standard model.
- ◆ Comprehensive program of accessories and options for customization.
- ◆ Complies with European safety standard EN 1570-1 – CE certified.
- ◆ 24 V DC control unit and operating device with deadman's switch.
- ◆ Safety spacing between all moving parts.
- ◆ IP54 approved electrical system
- ◆ Overload protection.
- ◆ Adjustable trap prevention safety trip bars on all four sides of the platform.
- ◆ The table is equipped with hose burst valves and mechanical locks for servicing and maintenance.
- ◆ Maintenance-free bearing surface.
- ◆ PLC control with possibility to program various functions is included for the standard model.
- ◆ User manual in 20 different languages.



PRODUCT INFORMATION

Model	Art.no	Capacity kg	Lift stroke mm	Closed height mm	Length mm	Width mm	Lift time sec	kW	Weight kg pack. incl	Notes
TR 501	609945	500	600	160	900	700	12	0,37	140	
TR 1002	608179	1000	600	160	900	700	22	0,37	145	
TL 1000	34964	1000	820	180	1300	700	15	0,75	185	Stainless
TL 1000B	32920	1000	820	180	1300	800	15	0,75	190	
TL 1000XB	32925	1000	820	180	1300	1000	15	0,75	210	
TL 1000SS	33830	1000	820	350	1300	800	48	0,37	220	
TL 1001B	33024	1000	820	180	1200	800	15	0,75	180	
TL 2000	22010	2000	820	200	1300	800	17	1,5	237	
TL 2000B	22011	2000	820	200	1300	1000	17	1,5	249	
TL 2000XB	512633	2000	820	200	1300	1200	17	1,5	275	
TL 3000	33560	3000	820	250	1300	800	26	1,5	300	
TB 2000	22253	2000	1000	220	1500	1000	26	1,5	260	
TB 2000B	22254	2000	1000	220	1500	1200	26	1,5	280	
TM 1000	32970	1000	1100	180	1700	700	27	0,75	260	
TM 1500	22012	1500	1100	230	1700	1000	17	1,5	311	
TM 1500B	33145	1500	1100	230	1700	1200	17	1,5	337	
TM 3000	33180	3000	1100	250	1700	900	27	1,5	386	
TM 6000*	33810	6000	1100	300	1700	900	32	3,0	550	
TA 1000	33335	1000	1300	200	2000	800	16	1,5	300	
TA 2000	34230	2000	1300	230	2000	900	30	1,5	400	
TA 4000	33860	4000	1300	350	2000	1200	27	3,0	650	
TA 10000*	33240	10000	1100	600	2000	1100	40	4,0	1200	
TS 2000	33720	2000	1500	250	2200	1200	27	1,5	524	
TS 2000B	33725	2000	1500	250	2200	1500	27	1,5	580	
TS 4000	33430	4000	1500	350	2200	1200	27	3,0	700	
TS 4000B	33440	4000	1500	350	2200	1500	27	3,0	770	
TT 3000	32662	3000	1700	300	2500	1300	27	3,0	705	
TT 6000	33460	6000	1600	450	2500	1300	40	3,0	1190	
TT 10000*	33070	10000	1500	600	2500	1300	55	4,0	1550	
TP 3000	514564	3000	2000	400	3000	1500	38	3,0	1160	
TP 6000	33400	6000	2000	500	3000	1500	55	3,0	1375	
TV 10000*	33200	10000	2200	700	3600	1500	72	4,0	2900	
TF 3000	34090	3000	3600	500	5000	2000	60	4,0	2300	
TO 4000	33840	4000	4000	600	5600	1500	95	4,0	2500	

*External powerpack without cover

CE- or Type 2B declaration

We construct and manufacture our lift tables and lift trolleys in accordance with the basic requirements in the Lift table standards EN 1570-1 and the Lift trolley standards SS-EN ISO 3691-5:2009. We comply with the requirements in accordance with Machine, Low voltage and the EMC directive. The products are delivered after being tested with CE certification and the assurance of agreement or in certain cases the manufacturer's Type 2B declaration.

